

SAFETY DATA SHEET



MOTOR MEDIC® SILICONE BRAKE FLUID DOT 5

Version 2.4 Revision Date: 04/23/2025 SDS Number: 600000001425 Date of last issue: 04/10/2024
Date of first issue: 07/13/2018

SECTION 1. IDENTIFICATION

Product name : MM BF SILICN DOT5 6/32OZ
Product code : M4032/6

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : 720 Vaiden Drive, Hernando, MS 38632
Email Address :
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use


Recommended use : BRAKE FLUID
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : Suspected of causing cancer.

Precautionary statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

**MOTOR MEDIC® SILICONE BRAKE FLUID
DOT 5**

Version	Revision Date:	SDS Number:	Date of last issue: 04/10/2024
2.4	04/23/2025	600000001425	Date of first issue: 07/13/2018

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Tributylphosphate	126-73-8	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Seek medical advice.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Suspected of causing cancer.

**MOTOR MEDIC® SILICONE BRAKE FLUID
DOT 5**

Version	Revision Date:	SDS Number:	Date of last issue: 04/10/2024
2.4	04/23/2025	600000001425	Date of first issue: 07/13/2018

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national

**MOTOR MEDIC® SILICONE BRAKE FLUID
DOT 5**

Version 2.4 Revision Date: 04/23/2025 SDS Number: 600000001425 Date of last issue: 04/10/2024
Date of first issue: 07/13/2018

regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Tributylphosphate	126-73-8	TWA (Inhalable fraction and vapor)	5 mg/m ³	ACGIH
		TWA	0.2 ppm 2.5 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA Z-1
		TWA	0.2 ppm 2.5 mg/m ³	OSHA P0

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:

SAFETY DATA SHEET



MOTOR MEDIC® SILICONE BRAKE FLUID DOT 5

Version 2.4 Revision Date: 04/23/2025 SDS Number: 600000001425 Date of last issue: 04/10/2024
Date of first issue: 07/13/2018

Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : purple

Odour : mild

Odour Threshold : not determined

pH : not determined

: not determined

Boiling point/boiling range : > 260 °C

Flash point : > 120 °C

Evaporation rate : not determined

Flammability (solid, gas) : not determined

Self-ignition : not determined

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.985 hPa (25 °C)

Relative vapour density : not determined

Density : 8.22 lb/gal

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : not determined

Decomposition temperature : not determined

Viscosity
Viscosity, dynamic : not determined

**MOTOR MEDIC® SILICONE BRAKE FLUID
DOT 5**

Version	Revision Date:	SDS Number:	Date of last issue: 04/10/2024
2.4	04/23/2025	600000001425	Date of first issue: 07/13/2018

Viscosity, kinematic : 42.7 mm²/s (40 °C)
Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Hazardous polymerisation does not occur.
Conditions to avoid : No data available
Incompatible materials : Strong oxidizing agents
Strong bases
Hazardous decomposition products : Carbon oxides
Silicon oxides
Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method
Acute dermal toxicity : Acute toxicity estimate: 2,404 mg/kg
Method: Calculation method

Components:**Tributylphosphate:**

Acute oral toxicity : LD50 (Rat, male and female): 1,552 mg/kg
Acute inhalation toxicity : LC50 (Rat, male and female): > 4.242 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is minimally toxic after short term inhalation.
Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,100 mg/kg

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET



MOTOR MEDIC® SILICONE BRAKE FLUID DOT 5

Version 2.4 Revision Date: 04/23/2025 SDS Number: 600000001425 Date of last issue: 04/10/2024
Date of first issue: 07/13/2018

Product:

Remarks: May irritate skin.

Components:

Tributylphosphate:

Method: OECD Test Guideline 404
Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Tributylphosphate:

Result: Possibly irritating to eyes
Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Tributylphosphate:

Test Type: Open epicutaneous test
Species: Guinea pig
Result: Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Components:

Tributylphosphate:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

SAFETY DATA SHEET



MOTOR MEDIC® SILICONE BRAKE FLUID DOT 5

Version 2.4 Revision Date: 04/23/2025 SDS Number: 600000001425 Date of last issue: 04/10/2024
Date of first issue: 07/13/2018

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

SAFETY DATA SHEET



MOTOR MEDIC® SILICONE BRAKE FLUID DOT 5

Version	Revision Date:	SDS Number:	Date of last issue: 04/10/2024
2.4	04/23/2025	600000001425	Date of first issue: 07/13/2018

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SAFETY DATA SHEET




MOTOR MEDIC® SILICONE BRAKE FLUID DOT 5

Version 2.4 Revision Date: 04/23/2025 SDS Number: 600000001425 Date of last issue: 04/10/2024
Date of first issue: 07/13/2018

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 04/23/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN